

This self-adhesive film for sandblasting works is ideal to stencil on smooth surfaces such as works on glass or polished stones with medium exposure. The high durability of the adhesive ensures safe work on the surface. The production of sharp outlines and the removal without leaving any residues are guaranteed. This stencil film allows different glass creations like relief structures, letterings, logos or satin finish of surfaces.

Thanks to its flexibility this film is ideal for the use in computerised cutting of letterings, logos and shapes.

## Technical Data

### Construction

<b>Face Film</b>	Special PVC
<b>Thickness</b>	~ 230 µm
<b>Adhesive</b>	Acrylic pressure adhesive square
<b>Release Liner</b>	Silicone cardboard square weight: ~ 140 g/m <sup>2</sup>

### Adhesive

<b>Adhesive Strength: (ASTMD-903)</b>	Immediately After 1 week	~ 2.5 N/25 mm ~ 7.0 N/25 mm
<b>Dimensional stability:</b>	2 hours with 70° C on acrylic glass	No longitudinal or lateral contraction
<b>Tensile Strength:</b>	DIN 53 455	Longitudinal: ~ 150 % Lateral: ~ 170 %
<b>Combustibility:</b>	Stuck on aluminium	The film is self-extinguishing
<b>Temperature:</b>	Application Temperature: Service Temperature Range:	min. 15°C -30 °C up to +80 °C

### Processing

**Application:** Dry or wet application. Longer application processes and high temperatures increase the adhesive strength.

**Storage Life:** Before application the films can be stored for minimum 3 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or hanging wall racks.